


TAPE STRUCTURE



PRODUCT DESCRIPTION

Backing:

- Embossed PVC.

Adhesive:

- Rubber.

Colour:

- Yellow.

621

PVC masking tape – embossed.

APPLICATION

- Protection with plastering, carpentry during joinery and painting.
- Effective protection during painting and making colour patterns of external walls.
- Masking and joining elements outside or inside buildings, suitable especially for masking during plastering.

FEATURES AND ADVANTAGES

- UV resistant.
- Resistant to chemicals, moisture and aging.
- Waterproof.
- Easy to apply.
- Easy to tear during application without cutting tools (no cutting tools necessary).
- High tensile strength.
- During outside application doesn't leave adhesive stains until 21 days (in "full sun exposition").

USAGE

- Apply to the dry, clean and degreased surface, free from other contaminants.
- Optimal application temperature: $10 \div 40^{\circ}\text{C}$.
- During application use tension and pressure to smooth the tape by hand.

STORAGE

- To ensure the maximum product performance, store products in a dry, ventilated area in original packaging away from direct sunlight.
- Protect the products in original packaging against mechanical damage.
- The recommended storage temperature: $-5 \div 40^{\circ}\text{C}$.

PRODUCT FORM & SIZE AVAILABLE

30 mm x 25 m, 38 mm x 25 m, 50 mm x 25 m.

TECHNICAL DATA

Physical Properties	Unit	Value
Total thickness	mm	0.13
Temperature range	$^{\circ}\text{C}$	+80
Tensile strength	N/cm	min. 18
Adhesion to steel	N/cm	min. 1.5
Elongation	%	max 150

Product meets the applicable restrictions of RoHS Directive and Reach regulations.



ANTICOR Sp. z o.o. holds ISO 9001.