


HVAC PREMIUM

INDUSTRIAL TAPES

TAPE STRUCTURE



PRODUCT DESCRIPTION

Backing:

- Plasticized PVC film.

Adhesive:

- Synthetic rubber based.

Colour:

- White, black.

HVAC PREMIUM

Premium quality PVC installation tape.

APPLICATION

- Isolation and bundling wires.
- Repairing of damaged insulation.
- Strengthening of insulation in automotive electrical systems.

FEATURES AND ADVANTAGES

- All weather resistance including UV and ozone.
- Frost-resistant.
- Self-extinguishing.
- High resistant to water, soap solutions, oils, acids, alkalis, and corrosive chemicals.
- Excellent performance over a wide range of temperature.
- Very good adhesion and high flexibility.
- Easy and fast application.
- Excellent electrical insulation.

USAGE

- Apply to the dry, clean, and degreased surface, free from other contaminants.
- Optimal application temperature: 10 ÷ 40°C.
- Wrap the tape with min. 50% overlap.
- During application use tension and pressure to smooth the tape by hand.

STORAGE

- Store the product in dry area in original packaging.
- Protect the cartons against mechanical damage.
- The recommended storage temperature: 5 ÷ 35°C.

PRODUCT FORM & SIZE AVAILABLE

50 mm x 18 m.

TECHNICAL DATA

Parameters	Unit	Value
Total thickness	mm	0.18
Breakdown voltage	kV/mm	min. 8.0
Dielectric strength	kV/mm	min. 8.0
Temperature range	°C	-18 ÷ 105
Tensile strength	N/cm	min. 30
Adhesion to steel	N/cm	min. 2.2
Elongation	%	min. 260

Product meets the applicable restrictions of RoHS Directive and Reach regulations. Meets EN 60454-3-1 (Type 11).



ANTICOR Sp. z o.o. holds the ISO 9001:2015 certificate.